



SCM300ASL PRO : 3-way active

- Features
- 34mm soft dome tweeter.
 - Twin full spec "SL" 15"/375mm bass drivers.
 - ATC 75mm "Super Dome" mid driver.
 - Rack-mount ATC 4 way grounded plane 850W amplifier.
 - Clip indication.
 - 6 year warranty.

Specifications

Drivers : HF 34mm, Mid 75mm, LF 2 x 375mm **Amplitude Linearity (± 2 dB) :** 50Hz-12kHz **Cut-off Frequencies (-6dB) :** 25Hz, 20kHz (free standing) 20Hz, 20kHz (soffit mounted)
Horizontal Dispersion : $\pm 80^\circ$, Coherent **Vertical Dispersion :** $\pm 10^\circ$, Coherent **Max. Continuous SPL (1 metre) :** 121 dB **Crossover Frequencies :** 380Hz, 3.5kHz
Input Connectors : Male XLR **Input Sensitivity :** 2V **Input Impedance :** Balanced $> 10k\Omega$ **Amplifier Output :** Bass 275+275W, Mid 200W, High 100W
Filters : Even Order Critically Damped **Overload Protection :** Active FET momentary gain reduction plus thermal tweeter protection
Front Panel Indicators : Power On indicator, Gain Reduction warning **Dimensions (HxWxD) :** 884 x 925 x 460mm (34.8" x 36.4" x 18.7") **Weight :** 140kg / 308lbs

Passive versions available. ATC reserves the right to vary products and specifications without prior notice.

